

# SPECIFICATIONS

## AccuPyc® II 1340 - Pycnometer



### ENVIRONMENT

Stable between 15 to 35 °C (59 to 96 °F)

**Temperature** Temperature-controlled AccuPyc: temperature stability is dependent upon specifications of the installed circulator. Recommended range: 15 to 50 °C (59 to 122 °F)

**Humidity** 20 to 80% relative, non-condensing

### PHYSICAL

<b>Height</b>	17.9 cm (7.0 in.), analysis modules for 1-, 10-, and 100-cm <sup>3</sup> units, and control module 25.9 cm (10.2 in.), 350-cm <sup>3</sup> analysis module 43.0 cm (17.0 in.), 2000-cm <sup>3</sup> analysis module
<b>Width</b>	27.3 cm (10.7 in.), control module 27.3 cm (10.7 in.), control module 27.0 cm (10.6 in.), 2000-cm <sup>3</sup> analysis module
<b>Depth</b>	36.2 cm (14.3 in.)
<b>Weight</b>	9.3 kg (20.5 lbs), control/analysis unit (1-, 10-, and 100-cm <sup>3</sup> units) 7.9 kg (17.4 lbs), analysis module (1-, 10-, and 100 cm <sup>3</sup> units) 10.5 kg (23.2 lbs), analysis module (350-cm <sup>3</sup> unit) 3.6 kg (8.0 lbs), control module 26.0 kg (57.0 lbs), 2000-cm <sup>3</sup> analysis module

### ELECTRICAL

<b>Voltage</b>	90 to 264 VAC
<b>Power</b>	30 VA
<b>Frequency</b>	50 to 60 Hz